PRATLEY®

RATLEY

10

COVERAGE 4 m^2/ℓ on porous surfaces.

Use only one coat of

paint instead

of three!

6-8 m²/ ℓ on non porous surfaces.

PRATLEY

Name and Post

5

Cat. no. 99026

5 Bucket

PLASTER-GRIP PRIMER

ADHESIVE: Pratley Plaster-Grip Primer renders almost any surface plasterable, even smooth surfaces like steel or glass!

SEALANT: It also saves paint by bonding and sealing porous surfaces prior to painting.

When plastering

It is useful on poor or porous substrates or on smooth surfaces like steel. For example, Pratliperl fireproof plaster can be applied to steel structures primed with Plaster-GripPrimer.

When painting

It saves paint by sealing porous surfaces. It also facilitates painting directly onto old lime (white wash) surfaces and the painting of galvanized iron.

DIRECTIONS-

- Stir before use.
- Paint or spray Pratley Plaster-Grip Primer onto the surface.
- Plaster-Grip Primer will become transparent in about 20 minutes.
- Plaster-Grip Primer remains tacky for approximately 30 minutes after becoming colourless.
- Plaster or patch work must commence as soon as the product becomes transparent, viz. *it must_still be tacky!*
- Plaster-Grip Primer will lose its efficacy if plastering is attempted after it dries completely (tack-free).
- Allow to dry completely (tack-free) before painting.

Bond

WARNING:- To prevent "whitening" do not use in ambient temperature below 10°C.

SOME SUGGESTED APPLICATIONS

Plaster

Cat. no. 99024

10ℓ Bucket

- Prime smooth steel before plastering.
- Prime smooth concrete before plastering.
 Prime poor and absorbent old
- Prime poor and absorbent old walls before plastering.
- Prime steel then apply Pratliperl fireproof Plaster.



PAINT over Plaster-Grip Primer.

Paint
Prime Galvanized iron. Then paint directly.

- Prime newly plastered absorbent walls (saveup to two coats of paint).
- Prime old lime washed walls then paint directly with PVA.
- Prime onto PVA before applying oil based paint.
- Prime chipped corners and steps before patching.
- Prime concrete before applying floor topping screed.
- Even use as a wood glue.



Primer.



Primer

POLICY STATEMENT "The performance of our products must exceed all others on the World Market" K & M (ratty CEO

> 201 10/5/2010

Pratley (Pty) Ltd. P O Box 3055 • KENMARE 1745 • Gauteng South Africa • Tel.:+27 11 955-2190/8 • Fax: +27 11 955-3918 www.pratley.com

PLASTER over Plaster-Grip TILE over Plaster-Grip

pping