

Technical data: GSB 21-2 RCT Professional

Rated power input	1.300 W
No-load speed	0 – 900 / 3.000 rpm
Power output	695 W
Weight	2,9 kg
Rated speed	900 – 3.000 rpm
Torque (soft screwdriving applications)	43,0 / 20,5 Nm
Rated torque	7,8 / 2,6 Nm
Drill spindle connecting thread	1/2" – 20 UNF
Chuck capacity	1,5 – 13 mm
Impact rate at no-load speed	0 – 15.300 / 51.000 bpm
Max. torque	43,0 / 20,5 Nm
Drilling range	
Drilling dia. in concrete	22 / 13 mm
Drilling dia. in wood	40 / 25 mm
Drilling dia. in steel	16 / 10 mm
Drilling dia. in masonry	24 / 16 mm

Functions

- Multiple gears
- Forward/reverse operation
- Electronic
- Constant Electronic
- Power Control
- Auto-Lock
- Softgrip
- Overload clutch

Noise/vibration information

Measured values determined according to EN 60745.
Total vibration values (vector sum of three directions)

Thread-cutting	
Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s ²
Screwdriving	
Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s ²
Impact drilling in concrete	
Vibration emission value ah	14.6 m/s ²
Uncertainty K	1.8 m/s ²
Drilling in metal	
Vibration emission value ah	5.6 m/s ²
Uncertainty K	1.5 m/s ²

The A-rated noise level of the power tool is typically as follows: Sound pressure level 95 dB(A); Sound power level 106 dB(A). Uncertainty K= 3 dB.