



GA7020 & GA9020K

180mm & 230mm Angle Grinders

2 200W

Shaft lock system
For safe and easy replacement of abrasive wheel.

Large rubber tool rest
Protects workpiece from scratches

Soft grip
For more comfort and control.

Protective zig-zag varnish & Protective powder varnish
Protective zig-zag varnish on armature coil.
Protective powder varnish-coating on field coil.

Side grip
Can be attached in one of three positions to suit left or right handed operators.

Machined spiral bevel gear
For higher durability than sintered gears, as well as smoother and quieter operation.

Bearing durability
Uses ball bearing reinforced with nylon retainer for more bearing durability on the drive end of the armature.

Rotatable gear housing
Can be positioned at every 90 degrees to suit most cutting and grinding operations.

SPECIFICATIONS:

	GA7020	GA9020
Maximum Capacities:		
Depressed centre wheel	180mm	230mm
Continuous rating input	2,200W	2 200W
No load speed	8 500 r/min	6 600 r/min
Overall length	473mm	473mm
Net weight	5.5kg	5.9kg
Power supply cord	2.5m	2.5m
Carbon brush	AC204	AC204

FEATURES:

Double insulation. GA9020K comes with Carry Case. GA7020 and GA9020 does NOT come with Carry Case.

STANDARD EQUIPMENT:

Lock nut wrench & grip

Tool does not come with depressed centre wheel

OPTIONAL ACCESSORIES

Description	Part No.
Diamond blade segmented	A-84137
Diamond blade, corrugated	A-84171
Inner flange 13-42 DIN45	224298-7
Lock nut 14-45	224543-0
Lock nut wrench 35 large 2 pin	782407-9
Rubber pad & nut	B-00876
Safety cutting flange	191845-8
Sanding lock nut 14 -48	224515-5
Special lock nut 14-45 (Prevents lock-up)	192567-3

