

**Technical data: GNA 3-5 Professional**

---

Material that can be processed	Steel up to 400 N/mm <sup>2</sup> at 3.5 mm
Cutting track width	6 mm
Pre-drilling for interior cutout	41 mm
Smallest radius	70 mm
Stroke rate, load	670 spm
Stroke rate at no load	1.000 spm
Weight	3,5 kg
Length	292 mm
Height	117 mm
Cutting capacity in steel (400 N/mm <sup>2</sup> ), max.	3,5 mm
Cutting capacity in steel (600 N/mm <sup>2</sup> ), max.	2,4 mm
Cutting capacity in steel (800 N/mm <sup>2</sup> ), max.	1,6 mm
Cutting capacity in aluminium (200 N/mm <sup>2</sup> ), max.	4,0 mm
<b>Electric specifications</b>	
Rated power input	620 W
Power output	340 W

**Noise/vibration information**

---

Measured values determined according to EN 60745  
Total vibration values (vector sum of three directions)

Vibration emission value ah 9.0 m/s<sup>2</sup>

Uncertainty K 1.5 m/s<sup>2</sup>

The A-rated noise level of the power tool is typically as follows: Sound pressure level 80 dB(A); Sound power level 80 dB(A). Uncertainty K= 3 dB.