

Technical data: GSB 21-2 RE Professional

| | |
|---|-------------------------|
| Rated power input | 1.100 W |
| No-load speed | 0 – 900 / 3.000 rpm |
| Power output | 630 W |
| Weight | 2,9 kg |
| Rated speed | 0 – 580 / 1.900 rpm |
| Torque (soft screwdriving applications) | 40,0 / 14,5 Nm |
| Rated torque | 9,6 / 3,2 Nm |
| Drill spindle connecting thread | 1/2" – 20 UNF |
| Chuck capacity | 1,5 – 13 mm |
| Impact rate at no-load speed | 0 – 15.300 / 51.000 bpm |
| Max. torque | 40,0 / 14,5 Nm |
| Drilling range | |
| Drilling dia. in concrete | 22 / 13 mm |
| Drilling dia. in wood | 40 / 25 mm |
| Drilling dia. in steel | 16 / 8 mm |
| Drilling dia. in masonry | 24 / 16 mm |

Functions

- Multiple gears
- Forward/reverse operation
- Electronic
- Auto-Lock
- Softgrip
- Overload clutch

Noise/vibration information

Measured values determined according to EN 60745.
Total vibration values (vector sum of three directions)

| | |
|------------------------------------|-----------------------|
| Thread-cutting | |
| Vibration emission value ah | 2.5 m/s ² |
| Uncertainty K | 1.5 m/s ² |
| Screwdriving | |
| Vibration emission value ah | 2.5 m/s ² |
| Uncertainty K | 1.5 m/s ² |
| Impact drilling in concrete | |
| Vibration emission value ah | 14.6 m/s ² |
| Uncertainty K | 1.8 m/s ² |
| Drilling in metal | |
| Vibration emission value ah | 5.6 m/s ² |
| Uncertainty K | 1.5 m/s ² |

The A-rated noise level of the power tool is typically as follows: Sound pressure level 95 dB(A); Sound power level 106 dB(A). Uncertainty K= 3 dB.